



MK-1600 GAS SERIES WALK-BEHIND CONCRETE SAWS

- One-piece box construction chassis made from 3/16" hot-rolled steel will not flex during operation
- Powder-coated chassis resists peeling & corrosion
- · Cast-aluminum hinged blade guard
- Stainless steel water distribution system supplies water to both sides of blade
- 18" blade guard mounts on the right-hand side of the Standard model saw and cuts within 2" of wall or curb
- 1" blade shaft supported by two heavy-duty, self-aligning pillow block bearings
- · Depth control assembly engineered for smooth, controlled blade insertion
- Durable 8" x 2-1/4" non-slip rubber wheels with maintenance-free hubs & roller bearings
- Positive-locking depth control mechanism
- Premium saws include built-in depth gauge, tach/hour meter and lifting bail. Blade guard mounts
 on both the left and right side of the saw
- One-year limited warranty

Recommended Diamond Blades

MK-505 Premium Grade Cured Concrete

Size	Part #	
18"	129072	
$\overline{}$		

MK-605W Premium Grade
Green Concrete

Size Part #		
18"	150169	
$\overline{\frown}$		

MK-699D *Premium Grade* Asphalt & Green Concrete

Size	Part #		
18"	153491		

MK-705W Premium Grade Asphalt

Size	Part #	
18"	133850	





1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158 www.mkdiamond.com | customer_service@mkdiamond.com



www.facebook.com/mkdiamondproducts



www.instagram.com/mkdiamondproducts





MK-1613H Standard

MK-1600 Series Walk-Behind Gas Concrete Saw

All MK-1600 Series walk-behind concrete saws feature a one-piece box construction chassis made from 3/16" hot-rolled steel that will not flex during operation. Powder-coated chassis resists peeling and corrosion. Cuts within 2" of wall or curb. One-year limited warranty.

Arbor Size	1" (25 mm)		
Blade Capacity	18" (457 mm)		
Depth of Cut	6-5/8" (168 mm)		
L x W x H (inches) L x W x H (mm)	42" x 25" x 39" 1,067 x 635 x 991		
Model	MK-1609H Standard	MK-1613H Standard	MK-1613H Premium
Engine	Honda (Gas)	Honda (Gas)	Honda (Gas)
Power	GX270*	GX390 Cyclone*	GX390 Cyclone*
Weight	210 lbs. (95 kg)	223 lbs. (101 kg)	233 lbs. (106 kg)
Includes			Built-in Depth GaugeBuilt-in Tach/Hour MeterLifting Bail
Part#	157867	160832	160772
Optional	Lifting Bail	6.5 Gallon Water Tank Kit	Tach/Hour Meter
Part#	157745	172622	153877

^{*}Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating.

MARNING: Cancer and Reproductive Harm - www.p65warnings.ca.gov



Cast aluminum hinged blade guard



Positive-locking depth control mechanism



Optional 6.5 gallon Water Tank Kit includes lifting bail