



Blade not included
MK-1610B Premium 3 Phase

MK-1600 ELECTRIC SERIES FEATURES

- One-piece box construction chassis made from 3/16" hot-rolled steel will not flex during operation
- Powder-coated chassis resists peeling & corrosion
- Cast-aluminum hinged blade guard
- Stainless steel water distribution system supplies water to both sides of blade
- 18" blade guard mounts on both left- or right-hand side of saw and cuts within 2" of wall or curb
- 1" blade shaft supported by two heavy-duty, self-aligning pillow block bearings
- Depth control assembly engineered for smooth, controlled blade insertion
- Durable 8" x 2-1/4" non-slip rubber wheels with maintenance-free hubs & roller bearings
- Positive-locking depth control mechanism
- Built-in depth gauge, power cord with connector and lifting bail
- One-year limited warranty

Recommended Diamond Blades

MK-505 *Standard Grade*
Cured Concrete

Size	Part #
18"	129072



MK-605W *Premium Grade*
Green Concrete

Size	Part #
18"	150169



MK-699D *Premium Grade*
Asphalt & Green Concrete

Size	Part #
18"	153491



MK-705W *Standard Grade*
Asphalt

Size	Part #
18"	133850



1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158

www.mkdiamond.com | customerservice@mkdiamond.com



<https://www.facebook.com/mkdiamondproducts>



<https://twitter.com/MKDiamond>



MK Diamond Products, Inc.



Blade not included
MK-1610B Premium Single Phase

MK-1600 SERIES Walk-Behind Electric Concrete Saw

All MK-1600 Series walk-behind concrete saws feature a one-piece box construction chassis made from 3/16" hot-rolled steel that will not flex during operation. Powder-coated chassis resists peeling and corrosion. The blade guard cuts within 2" of wall or curb. One-year limited warranty.

Model	MK-1605B Premium	MK-1610B Premium	MK-1610B Premium	MK-1610B Premium
Engine	ABB Baldor (Electric)	ABB Baldor (Electric)	ABB Baldor (Electric)	ABB Baldor (Electric)
Power	5 Hp 240V 1 PH	10 Hp 230V 3 PH	10 Hp 480V 3 PH	10 Hp 230V 1 PH
Arbor Size	1" (25 mm)	1" (25 mm)	1" (25 mm)	1" (25 mm)
Blade Capacity	18" (457mm)	18" (457mm)	18" (457mm)	18" (457mm)
Depth of Cut	6-5/8" (168 mm)	6-5/8" (168 mm)	6-5/8" (168 mm)	6-5/8" (168 mm)
L x W x H (inches)	42" x 25" x 39"	42" x 25" x 39"	42" x 25" x 39"	42" x 25" x 39"
L x W x H (mm)	1,067 x 635 x 991	1,067 x 635 x 991	1,067 x 635 x 991	1,067 x 635 x 991
Weight	275 lbs. (125 kg)	275 lbs. (125 kg)	275 lbs. (125 kg)	275 lbs. (125 kg)
Includes	<ul style="list-style-type: none"> • Built-in Depth Gauge • Power Connector • Lifting Bail 	<ul style="list-style-type: none"> • Built-in Depth Gauge • Power Connector • Lifting Bail 	<ul style="list-style-type: none"> • Built-in Depth Gauge • Power Connector • Lifting Bail 	<ul style="list-style-type: none"> • Built-in Depth Gauge • Power Connector • Lifting Bail
Part#	168099	167426	167427	168611

Optional	6.5 Gallon Water Tank
Part#	157852

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | www.mkdiamond.com | F 310.539.5158

© 2018 MK Diamond Products, Inc. All Rights Reserved. Images and specifications are subject to change without notice. MK-1600 Electric Series Part# AP080161 (09/18)