



**MK Diamond Products, Inc.**



MK-1613H Premium

## **MK-1600 GAS SERIES WALK-BEHIND CONCRETE SAWS**

- One-piece box construction chassis made from 3/16" hot-rolled steel will not flex during operation
- Powder-coated chassis resists peeling & corrosion
- Cast-aluminum hinged blade guard
- Stainless steel water distribution system supplies water to both sides of blade
- 18" blade guard mounts on both left- or right-hand side of saw and cuts within 2" of wall or curb
- 1-1/4" blade shaft supported by two heavy-duty, self-aligning pillow block bearings
- Depth control assembly engineered for smooth, controlled blade insertion
- Durable 8" x 2-1/4" non-slip rubber wheels with maintenance-free hubs & roller bearings
- Positive-locking depth control mechanism
- Built-in depth gauge, power cord with connector and lifting bail
- One-year limited warranty



**MK Diamond Products, Inc.**



MK-1613H Standard

### MK-1600 Series Walk-Behind Gas Concrete Saw

All MK-1600 Series walk-behind concrete saws feature a one-piece box construction chassis made from 3/16" hot-rolled steel that will not flex during operation. Powder-coated chassis resists peeling and corrosion. The blade guard mounts on both the left and right side of saw and cuts within 2" of wall or curb. One-year limited warranty.

<b>Arbor Size</b>	1" (25 mm)
<b>L x W x H (inches)</b>	42" x 25" x 39"
<b>L x W x H (mm)</b>	1,067 x 635 x 991

	Model MK-1609H Standard	MK-1613H Standard	MK-1613H Premium
<b>Engine</b>	Honda (Gas)	Honda (Gas)	Honda (Gas)
<b>Power</b>	GX240 Cyclone*	GX390 Cyclone*	GX390 Cyclone*
<b>Blade Capacity</b>	16" (406 mm)	18" (457 mm)	18" (457 mm)
<b>Depth of Cut</b>	5-5/8" (143 mm)	6-5/8" (168 mm)	6-5/8" (168 mm)
<b>Weight</b>	210 lbs. (95 kg)	223 lbs. (101 kg)	233 lbs. (106kg)
<b>Includes</b>	• 14" Dry Cutting Diamond Blade	• 14" Dry Cutting Diamond Blade	• 14" Dry Cutting Diamond Blade • Built-in Depth Gauge • Built-in Tach/Hour Meter • Lifting Bail
<b>Part#</b>	157867	160832	160772

<b>Optional</b>	6.5 Gallon Water Tank
<b>Part#</b>	157852

\*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating.



Cast aluminum hinged blade guard



Positive-locking depth control mechanism



Optional water tank is available