



Blade not included.

MK-3000B ELECTRIC SERIES FEATURES

- Totally enclosed and sealed blade shaft with continuous oil bath lubrication system
- Quick release, auto-latching bayonet mount blade guard
- Three position adjustable solid steel handlebars
- Blade guard uses "ride on the blade" water tubes for superior water delivery and blade cooling
- Dual arbor design for left or right side mounting of blade and blade guard
- Rigid frame front pointer with high visibility guide wheel for accurate tracking
- Built-in ammeter to monitor load
- Ergonomic FNR traverse control for ease of operation
- Depth of cut indicator positioned for easy access
- Blade guard has garden hose style connector for quick disconnecting
- Removable rear panel for easy service
- Seven 3VX belts from engine to blade shaft
- Electric leadscrew for positive adjustment of cutting depth
- Wide front wheel base increases stability and allows ramp loading/unloading
- Easy access emergency stop control
- Water control level allows operator to adjust rate of water flow to blade guard
- Eaton model 6 hydrostatic transmission coupled to a MK trans-axle
- Built-in lifting bail for easy maneuverability
- Travel speed 0-220 FPM forward, 0-100 FPM reverse
- Neutral start switch to prevent starting with transmission in gear
- Transmission can be disengaged from axle to allow saw to be pushed manually
- Made in U.S.A.

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158

www.mkdiamond.com | customer_service@mkdiamond.com



<https://www.facebook.com/mkdiamondproducts>



<https://twitter.com/MKDiamond>



Blade not included.

MK-3000B Pro Electric Self-Propelled Concrete Saws

The MK-3000 Electric Saw provides a solution for those environments and situations where electric power is the right choice, whether for indoor use or simply operator preference. The saw utilizes a three-phase, 20 Hp, electric motor in 230V or 460V to match the user's need. The saw features the same raise/lower system, self-propelled transmission and control set as other MK-3000s. An ammeter is provided to help monitor load when cutting. One-year limited warranty.

Switch	IP 65 IEC Across the line starter			
Travel Speed	0-220 FPM Forward, 0-100 FPM Reverse			
Arbor	1" with 3/8" dirve pin			
L x W x H (inches)	57" x 29 3/4" x 43"			
L x W x H (mm)	1,448 x 756 x 1,092mm			
Motor	Electric			
Weight	700 lbs. (318kg)			
Model	MK-3020B	MK-3020B	MK-3026B	MK-3026B
Size	20" (508mm)	20" (460mm)	26" (660mm)	26" (660mm)
Power	20 Hp 230V 3Ph	20 Hp 460V 3Ph	20 Hp 230V 3Ph	20 Hp 460V 3Ph
Blade RPM	2,580	2,580	2,030	2,030
Depth of Cut	7-1/2" (191mm)	7-1/2" (191mm)	10-1/2" (267mm)	10-1/2" (267mm)
Part#	167428-20	167429-20	167428-26	167429-26
Model	MK-3030B	MK-3030B		
Size	30" (762mm)	30" (762mm)		
Power	20 Hp 230V 3Ph	20 Hp 460V 3Ph		
Blade RPM	1,680	1,680		
Depth of Cut	12-1/2" (318mm)	12-1/2" (318mm)		
Part#	167428-30	167429-30		

Blade not included.

⚠ WARNING: Cancer and Reproductive Harm - www.p65warnings.ca.gov



20HP, 3 Phase, TEFC electric motor, providing 30ft-lb of torque



Three position adjustable solid steel handle bars



7 3VX belts from engine to center shaft