



Blade not included  
MK-5009G

## MK-5000 GAS SERIES FEATURES

- Precision screw feed mechanism allows the cutting head to be easily raised or lowered to the precise cutting depth required
- Self-leveling blade guard provides optimum blade coverage for operator safety
- Open-back design allows for material up to 20" long to be cut
- Conveyor cart built from heavy-duty cast aluminum
- Adjustable water supply for maximum blade protection
- Built-in tie-downs for safer saw transport
- Ergonomically designed handle for reduced operator fatigue
- Engine attachment is via four vibration isolation mounts
- Belt driven, self-priming centrifugal water pumps can be disengaged for dry cutting
- Heavy-duty built-in forklift brackets allow lift to approach from the front or either side of the saw
- One-year limited warranty

### Recommended Diamond Blades

**MK-62GSPV** *ProGranite Silent Core*

Size	Part #
14"	154591
20"	155902



**MK-925DSLX** *Supreme Hard Material Silent Core*

Size	Part #
20"	160971
24"	168050



1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158  
www.mkdiamond.com | customer\_service@mkdiamond.com



[www.facebook.com/mkdiamondproducts](http://www.facebook.com/mkdiamondproducts)



[www.instagram.com/mkdiamondproducts](http://www.instagram.com/mkdiamondproducts)




Blade not included  
MK-5009G

### MK-5000 Gas Series Wet Cutting Block Saws

The MK-5000 Series gas block saw provides power and jobsite performance when a gas-powered saw is the only option. Equipped with a self-priming water pump, isolation mounts to prevent operator fatigue due to engine vibration and an ergonomic control handle. One-year limited warranty.

<b>Length of Cut</b>	20" (508 mm)					
<b>L x W x H (inches)</b>	60" x 26" x 72"					
<b>L x W x H (mm)</b>	1,524 x 660 x 1,826					
<b>Includes</b>	<ul style="list-style-type: none"> <li>• Centrifugal Water Pump</li> <li>• Rip Guide</li> </ul>					
<b>Model</b>	MK-5009G			MK-5013G		
<b>Engine</b>	Honda (Gas)			Honda (Gas)		
<b>Power</b>	GX270 Cyclone			GX390 Cyclone		
<b>Weight</b>	498 lbs. (225 kg)			513 lbs. (233 kg)		
	<b>Blade Guard Options</b>			<b>Blade Guard Options</b>		
<b>Size</b>	14"	20"	24"	14"	20"	24"
<b>Depth of Cut</b>	5" (127 mm)	8" (203 mm)	10" (254 mm)	5" (127 mm)	8" (203 mm)	10" (254 mm)
<b>Part#</b>	158935-14	158935	158935-24	158936-14	158936	158936-24

**⚠ WARNING:** Cancer and Reproductive Harm - [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)



NEMA 4X rated 3PH Motor Starter is proof against rain and hose directed water. Magnetic disconnect prevents accidental restart if electrical current is disrupted



Self-priming centrifugal water pump



Heavy-duty isolation mounts to prevent operator fatigue due to engine vibration