



Blade not included

MK-5010 Super-Matic Features

- Heavy-duty blade shaft and bearings for trouble free performance
- Heavy-duty conveyor cart to support additional weight
- Operator safety handle on conveyor cart
- Advanced blade guard system for added operator safety
- Optional variable speed motor controller available on 460 volt saw
- Precision screw feed mechanism allows the cutting head to be easily raised or lowered to the precise cutting depth required
- Open-back design allows for material up to 20" long to be cut
- Conveyor cart built from heavy-duty cast aluminum
- 3 phase saws are equipped with NEMA 4X rated 3PH Motor Starter
- Adjustable water supply for maximum blade protection
- Built-in tie-downs for safer saw transport
- Ergonomically designed handle for reduced operator fatigue
- Spherical rod ends are used to maintain proper cutting head alignment
- Heavy-duty built-in forklift brackets allow lift to approach from the front or either side of the saw
- Made in the USA
- One-year limited warranty

Recommended Diamond Blades

MK-62GSPV *ProGranite Silent Core*

Size	Part #
20"	155902



MK-925DSLX *Supreme Hard Material Silent Core*

Size	Part #
20"	160971
24"	168050



1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158

www.mkdiamond.com | customer_service@mkdiamond.com



www.facebook.com/mkdiamondproducts



www.instagram.com/mkdiamondproducts



Blade not included

MK-5000 Super-Matic Series Wet Cutting Industrial Block Saws

The MK-5000 Series of heavy-duty industrial block saws have been designed to meet the demands of industrial production. 1" self-aligning pillow block bearings, along with a host of innovative operator conveniences and safety features, boost productivity and efficiency. One-year limited warranty.

Motor	Electric	
Blade Guard	24" (610 mm)	
Length of Cut	20" (508 mm)	
L x W x H (inches)	53" x 26" x 63"	
L x W x H (mm)	1,346 x 660 x 1,600	
Includes	<ul style="list-style-type: none"> • Electric Water Pump • Rip Guide 	
Model	MK-5010S Super-Matic	MK-5010T Super-Matic
Power	10 Hp, 240V 1Ph / 3Ph 10 Hp, 460V 3Ph	10 Hp, 460V 3Ph 10 Hp, 575V 3 Ph
Weight	513 lbs. (233 kg)	513 lbs. (233 kg)
Depth of Cut	10" (254 mm)	10" (254 mm)
208-230V Part#	166929 (1Ph)	166930 (3Ph)
460V Part#	•	166931 (3Ph)
575V Part#	•	169335 (3Ph)

(Motor available in other electrical configurations.)


 **WARNING:** Cancer and Reproductive Harm - www.p65warnings.ca.gov



Heavy-duty 6 wheel conveyor cart to support additional weight



Supermatic features an advanced Blade Guard System for added operator safety



NEMA 4X rated 3PH Motor Starter is proof against rain and hose directed water. Magnetic disconnect prevents accidental restart if electrical current is disrupted.