



MK Diamond Products, Inc.



Scan for Video



Blade not included

SRX-2000 FEATURES

- “Upcut” blade rotation facilitates keeping debris out of the joint
- Triangular shaped arbor
- Oil-bath blade shaft for maintenance free operations
- Vacuum port for easy connection to dust control systems
- Easy release depth control lever
- Remotely mounted throttle and stop switch for quick operator access
- Folding handle bar for compact transport and storage
- Three VX belt drive system
- Easily removed blade guard cover provides quick access for blade changes and inspection
- 4-inch wide, polyurethane wheels for non-marking
- Build-in Tach hour meter
- Skid plate minimizes joint chipping and spalling
- Lifting point for easy transport
- Remote mounted pointer control allows for full operation from the handlebar

Recommended Diamond Blades - Dry Cutting

GC-10 (purple)

Ultra Hard Aggregate



Size	Part #
10" x .100"	172620

GC-30 (red)

Medium / Hard Aggregate



Size	Part #
10" x .100"	171953
10" x .125"	171954



GC-55 (yellow)

Medium / Soft Aggregate

Size	Part #
10" x .100"	171973

GC-20 (green)

Hard Aggregate



Size	Part #
10" x .100"	171942
10" x .125"	171943

GC-35 (orange)

Medium Aggregate



Size	Part #
10" x .100"	171963
10" x .125"	171964

Replacement stainless steel skid plate part # 171287, replacement steel skid plate part # 171284.



MK Diamond Products, Inc.



Blade not included



SRX-2000 Green Concrete Saw

The self-propelled SRX-2000 dry cutting saw is engineered for early entry sawing of crack control joints within one to two hours of concrete finishing. The blade guard features a vacuum port to control dust when dry cutting. One year limited warranty.

Model	SRX-2000H	SRX-2000HE
Engine	Honda (Gas)	Honda (Gas)
Starter	Pull	Electric
Power	GX-270 Cyclone*	GX-270 Cyclone*
Blade Capacity	10" (254 mm)	10" (254 mm)
Depth of Cut	1-5/8" (41 mm)	1-5/8" (41 mm)
Arbor	Triangular	Triangular
L x W x H (inches)	82" x 24" x 43-1/2"	82" x 24" x 43-1/2"
L x W x H (mm)	2,083 x 610 x 1,105	2,083 x 610 x 1,105
Weight	286 lbs. (129.7 kg)	295 lbs. (133.8 kg)
Includes	Skid plate	Skid plate
Part#	172235	172235-E



Anti-spall, quick change skid plate



Vacuum port for easy connection to dust control systems



Folding handle bar for compact transport and storage

*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating. Blade not included.

⚠ WARNING: Cancer and Reproductive Harm - www.p65warnings.ca.gov

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158

www.mkdiamond.com | customerservice@mkdiamond.com



<https://www.facebook.com/mkdiamondproducts>



<https://twitter.com/MKDiamond>