



Blade not included
MK-2013HE

MK-20 SERIES FEATURES

- One-piece box construction chassis made from 3/16" hot-rolled steel will not flex during operation
- Powder-coated chassis resists peeling & corrosion
- Cast-aluminum hinged blade guard
- Stainless steel water distribution system supplies water to both sides of blade
- Blade guard mounts on both left- or right-hand side of saw and cuts within 2" of wall or curb
- 1-3/16" blade shaft supported by two heavy-duty, self-aligning pillow block bearings
- Depth control assembly engineered for smooth, controlled blade insertion
- Built-in tach/hour meter
- Depth feed gauge indicator
- Heavy-duty hydro static transmission with variable speed drive
- Durable 8" x 2 1/4" non-slip rubber wheels with maintenance-free hubs & roller bearing
- Forward travel speed: 0-80'/minute

Recommended Diamond Blades

MK-505 *Supreme Grade*
Cured Concrete

Size	Part #
16"	139238
18"	129072



MK-615W *Premium Grade*
Asphalt over Concrete

Size	Part #
16"	150231
18"	150232



MK-710W *Supreme Grade*
Asphalt

Size	Part #
16"	152646
18"	139089



MK-762DMX *Supreme Grade*
General Purpose/Concrete

Size	Part #
16"	161294
18"	161295



1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158

www.mkdiamond.com | customer_service@mkdiamond.com



www.facebook.com/mkdiamondproducts



www.instagram.com/mkdiamondproducts



MK Diamond Products, Inc.



Blade not included
MK-2013HE

MK-20 SERIES Self-Propelled Concrete Saw

MK-20 Series of concrete saws combine innovation and engineering to produce one of the lightest, midsize self-propelled concrete saws available. Key to the design is the featured box frame and channel that produces a rigid frame, which helps reduce sawing-induced vibrations. Engine weight is evenly distributed over the blade shaft for added stability and tracking. Depth control assembly is engineered for smooth, controlled blade insertion. One-year limited warranty.

Arbor Size	1" (25 mm)	
L x W x H (inches)	46" x 26" x 37"	
L x W x H (mm)	1,168 x 660 x 940	
Includes	• Lifting Bail	
Model	MK-2013HE	MK-2013HSP
Engine	Honda (Gas)	Honda (Gas)
Starter	Electric	Pull
Power	GX390 Cyclone*	GX390 Cyclone*
Blade Capacity	18" (457 mm)	18" (457 mm)
Depth of Cut	6-5/8" (168 mm)	6-5/8" (168 mm)
Weight	290 lbs. (132 kg)	290 lbs. (132 kg)
Part#	155714	156499
Optional	6.5 Gallon Water Tank	Water Pump Kit
Part#	157852	172896

*Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. MK Diamond Products makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy or the engine power rating. Users are advised to consult the engine manufacturer's owners manual and website for specific information regarding the engine power rating.

⚠ WARNING: Cancer and Reproductive Harm - www.p65warnings.ca.gov



Cast aluminum hinged blade guard



Blade guard mounts on either left- or right-hand side of saw and cuts within 2" of wall or curb



Easy to use control panel, includes built-in tach/hour meter.