





MK-5005S

## **MK-5000 ELECTRIC SERIES FEATURES**

- Precision screw feed mechanism allows the cutting head to be easily raised or lowered to the precise cutting depth required
- · Self-leveling blade guard provides optimum blade coverage for operator safety
- · Open-back design allows for material up to 20" long to be cut
- Conveyor cart built from heavy-duty cast aluminum
- 3 phase saws are equipped with NEMA 4X rated motor starter
- Adjustable water supply for maximum blade protection
- Built-in tie-downs for safer saw transport
- · Ergonomically designed handle for reduced operator fatigue
- · Heavy-duty built-in forklift brackets allow lift to approach from the front or either side of the saw
- One-year limited warranty

## **Recommended Diamond Blades**

MK-62GSPV Pro Granite Silent Core

| Size | Part # |  |  |  |
|------|--------|--|--|--|
| 14"  | 154591 |  |  |  |
| 20"  | 155902 |  |  |  |
| 20"  | 155902 |  |  |  |



Size Part # 14" 161283 20" 160971





1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158 www.mkdiamond.com | customer\_service@mkdiamond.com



www.facebook.com/mkdiamondproducts



www.instagram.com/mkdiamondproducts





## MK-5000 ELECTRIC SERIES Wet Cutting Block Saws

The MK-5000 Series of block saws set the quality standard for durability and maintenance-free operation. These saws are specially designed to provide the highest level of productivity, operator safety and convenience. Heavy-duty cast aluminum and steel parts ensure the finest value in the masonry and stone industry. One-year limited warranty.

 Motor
 Electric

 Length of Cut
 20" (508 mm)

 L x W x H (inches)
 53" x 26" x 63"

 L x W x H (mm)
 1,346 x 660 x 1,600

Includes • Electric Water Pump • Rip Guide

| Model          | MK-5005S          |             | MK-5005T          |             | MK-5007T          |             |              |
|----------------|-------------------|-------------|-------------------|-------------|-------------------|-------------|--------------|
| Power          | 5 Hp, 1PH         |             | 5 Hp, 3PH         |             | 7.5 Hp, 3PH       |             |              |
| Weight         | 445 lbs. (202 kg) |             | 451 lbs. (205 kg) |             | 485 lbs. (220 kg) |             |              |
| Blade Guard    | 14"               | 20"         | 14"               | 20"         | 14"               | 20"         | 24"          |
| Depth of Cut   | 5" (127 mm)       | 8" (203 mm) | 5" (127 mm)       | 8" (203 mm) | 5" (127 mm)       | 8" (203 mm) | 10" (254 mm) |
| 208-230V Part# | 160634-14         | 160634      | 160636-14         | 160636      | 160641-14         | 160641      | 160641-24    |
| 460V Part#     | _                 | _           | 160637-14         | 160637      | 160642-14         | 160642      | 160642-24    |

| Model          | MK-5010S          |           |        | MK-5010T          |           |        |
|----------------|-------------------|-----------|--------|-------------------|-----------|--------|
| Power          | 10 Hp, 1PH        |           |        | 10 Hp, 3PH        |           |        |
| Weight         | 503 lbs. (228 kg) |           |        | 503 lbs. (228 kg) |           |        |
| Blade Guard    | 24"               |           |        | 24"               |           |        |
| Depth of Cut   | 14"               | 20"       | 24"    | 14"               | 20"       | 24"    |
| 208-230V Part# | 169328-14         | 169328-20 | 169328 | 169330-14         | 169330-20 | 169330 |
| 460V Part#     | _                 | _         | _      | 169331-14         | 169331-20 | 169331 |

(Motor available in other electrical configurations.)

MARNING: Cancer and Reproductive Harm - www.p65warnings.ca.gov



Heavy-duty cast aluminum conveyor cart



Foot pedal for hands-free cutting head operation



Open-back design allow for materials up to 20" long to be cut