



- Fully enclosed high torque, fan-cooled motor
- Industrial 14.3 amp motor
- Easy access, heavy-duty 30 amp switch box
- · Permanently lubricated, dual-sealed, heavy-duty blade shaft bearings
- · Multi-position motor post and cutting head allows saw to be configure for convenient cutting of both large and small tiles
- Extended heavy-duty motor post provides a 13" throat depth
- Built-in water distribution system supplies water to both sides of blade
- · Variable height cutting head allows for plunge cuts
- · Accommodates 6" and 8" profile wheels
- · Micro V-belt drive for maximum horsepower transfer from motor to blade
- · Blade shaft lock for easy blade removal
- Linear-bearing and chrome plated guide-bar assembly ensure precise cutting
- · Cast aluminum table with non-slip molded neoprene surface
- · Cast aluminum blade guard and motor post
- One-piece reinforced zinc-plated steel frame
- High volume water pump
- · Made in the USA
- One-year limited warranty

1315 Storm Parkway, Torrance, CA 90501 | P 800.421.5830 | F 310.539.5158 www.mkdiamond.com | customer\_service@mkdiamond.com



www.facebook.com/mkdiamondproducts



www.instagram.com/mkdiamondproducts



## MK-101 PRO24 JCS 1-1/2 Hp, 10" Wet Cutting Tile Saw

The MK-101 Pro24 JCS has all the features of the MK-101; in addition it is equipped with a aluminum table with non-slip molded neoprene surface. The permanently lubricated blade shaft bearings provide years of maintenance-free operation. The blade guard has been engineered to provide optimal water flow and is wide enough to accommodate a profile wheel. One-vear limited warranty.



Multi-position motor post and cutting head for convenient cutting of various tile sizes

wheel. One-year limited warranty.	
Motor	Electric
Power	1-1/2 Hp, 120V
Blade Capacity	10" (254 mm)
Arbor Size	5/8" (16mm)
Depth of Cut	3" (76 mm)
Depth of Cut at 45°	2-3/8" (60 mm)
Length of Cut	24" (610 mm)
Diagonally Cut	18" (457 mm)
L x W x H (inches) L x W x H (mm)	48" x 24" x 29" 1,219 x 610 x 737
Weight	156 lbs. (71 kg)
Includes	<ul> <li>10" MK-225 Hot Dog Blade</li> <li>Water Pump</li> <li>Side Extension Table</li> <li>90° Protractor</li> <li>Dressing Stone</li> <li>Integrated Stand</li> <li>Dual 45° Flat Angle Guide</li> <li>Rip Guide</li> <li>45° Miter</li> </ul>
Part#	153243-JCS



Locking blade shaft for easy blade removal



MK-101 Pro24 JCS has an Integrated stand that allows operator to setup or transport in a matter of seconds

Motor available in other electrical configurations.

